



STEP2CleanPlan

Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 D: Smart Building Foundations & BAS Architecture

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







STEP2CleanPLAN

Agenda

- What is a Smart Building?
- BAS Architecture and Functions
- Key Components and Protocols
- Integration, SRI and Interoperability
- Smart Renovation and Commissioning
- Data, Optimization, and Policy Links
- Reflection Questions





What Defines a Smart Building?

- Automated, responsive, connected systems
- Real-time interaction with environment
- Enhanced efficiency and occupant experience








Design Goals of Smart Systems

- Reduce GHG and energy use
- Improve thermal, visual, acoustic comfort
- Enable building intelligence








Why Smart Buildings Matter for the EU

NEXT Black Sea Basin

- EPBD Recast includes SRI
- Support ZEB, EPC, Level(s)
- Public buildings must lead adoption








What is a Building Automation System?

NEXT Black Sea Basin

- Digital layer for HVAC, lighting, safety, access
- Centralized control of building systems
- Supports automation and optimization









STEP2CleanPLAN

- Monitoring and scheduling
- Remote access and control
- Fault detection and diagnostics

Core Functions of BAS







BAS vs BMS vs EMS

System	Key Focus	Components
BAS	Real-time control	HVAC, Lighting, Access, Shading
BMS	Centralized management	Fault detection, Fire Safety, Dashboards
EMS	Energy analytics & strategy	Meters, Carbon Reports, Portfolio Dashboards







Key Components in BAS

NEXT Black Sea Basin

- Sensors (CO₂, temp, presence)
- Controllers and actuators
- User interface and software














STEP2CleanPLAN

- Trigger ventilation, lighting, security
- Support comfort and safety
- Critical to smart responsiveness

Sensor Use Cases





Controllers and Logic Programming

- Setpoints, PID loops, safety interlocks
- Logic trees for scenario response
- Local + centralized control layers







Open vs Proprietary Protocols

STEP2CleanPLAN

NEXT Black Sea Basin

Open Protocols







Proprietary Systems

- Vendor-locked
- Limited interoperabilitiy



EU Preference → Open, Secure, Interoperarable





Interface Tools: Dashboards

- Real-time visualization of zones
- Mobile and browser-based control
- Role-based access and alerts








NEXT Black Sea Basin

STEP2CleanPLAN

- Avoid silos, improve performance
- Unified control = better coordination
- Scalable logic for future tech

System Integration Benefits








Interoperability Challenges

NEXT Black Sea Basin

STEP2CleanPLAN



Legacy systems, protocol clashes

IT/OT firewalls, cyber risk



Lack of skilled integrators






Smart Readiness Indicator (SRI)

ONE SINGLE SCORE CLASSIFIES

STEP2CleanPLAN

- Scores buildings on smart capabilities
- Domains: automation, optimization, reactivity
- Used in passports/logbooks + EPC upgrades



Source: REHVA






NEXT Black Sea Basin

Cloud + Edge BAS Trends

- Cloud = remote insight and updates
- Edge = real-time, local resilience
- EU projects use hybrid approaches









Smart Retrofitting Approaches

STEP2CleanPLAN

Wireless or IP-based retrofits








Commissioning and Quality Assurance

- Pre-functional + performance testing
- System calibration and validation
- Handover includes interface checks







Data Use for Optimization

- Trend analysis + auto-adjustment
- Anomaly detection = proactive O&M
- Input for Level(s), PHPP, EPC upgrades







How SRI Links to Level(s)

- Both focus on performance + user impact
- Support lifecycle and post-occupancy tracking
- Used in green finance frameworks







Conclusion & Takeaways

NEXT Black Sea Basin

- Smart buildings = EU-ready performance
- BAS is foundational to ZEB operation
- Open + interoperable = futureproof










- Which BAS feature matters most for your role?
- What stands in the way of smart integration?







Smart Retrofitting: Wireless & IP Protocols

STEP2CleanPLAN

NEXT Black Sea Basin

- Wireless: Zigbee, LoRa, BLE enable retrofit zones
- IP-based BAS reduces conduit and cabling needs
- Gateways bridge legacy and smart protocols









STEP2CleanPLAN

Thank you!

Q & A







STEP2CleanPlan


Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 H: Cybersecurity and Interoperability for Smart Building Systems

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







STEP2CleanPLAN

Agenda

- Cyber Threats in Smart Buildings
- BAS/IoT Vulnerabilities & Attack Vectors
- Protocol Conflicts & Interoperability Gaps
- Cybersecurity Standards & Semantic
 Governance
- Designing for Security & Lifecycle Monitoring
- Future-Proofing & Risk-Based Modernization
- Conclusion & Reflection






Why Cybersecurity Now?

STEP2CleanPLAN

- IoT adoption → attack surfaces grow
- FM systems now expose operations
- Breaches impact safety, comfort, data



https://www.researchgate.net/profile/Guowen-Li-5/publication/369131862/figure/fig4/AS:11431281236665506@1713279746038/Timeline-of-recently-reported-cyberattacks-on-buildings-and-their-physical-impacts.png





Vulnerabilities in BAS & IoT Systems

- Flat networks → lateral attacks
- Default credentials & open ports
- Unpatched firmware + outdated protocols








IoT Weaknesses in Smart Buildings

STEP2CleanPLAN

- Cloud dashboards poorly secured
- MQTT replay & fallback disruption
- Edge-to-cloud trust gaps



36 © 2023 Gartner, Inc. and/or its affiliates. All rights reserved. Gartner is a registered trademark of Gartner, Inc. and its affiliates.









Protocol Misalignment Risks

STEP2CleanPLAN







no standard handoff Translation loss & point mismatch

Gateways = single points of confusion






Semantic Conflicts in Integration

STEP2CleanPLAN

- Units, tags, meanings lost in translation
- Room temp vs duct temp confusion
- Fan status: binary vs enum



- Units, tags, meanings lost in translation
- Room temp vs duct temp confusion
- Fan status: binary vs enum

Units, tags, meanings lost in translation





Governance Failures & Blind Spots

- No integration plan → overlapping access
- Inconsistent naming → misfire APIs
- Semantic gaps = unmonitored zones








Cybersecurity Standards for Smart Buildings

STEP2CleanPLAN

NEXT Black Sea Basin

- IEC 62443: BAS lifecycle approach
- NIST CSF: Identify, Protect, Detect...
- ISO 27001: InfoSec management for FM
- BACnet/SC: Secure encrypted communication







Semantic Frameworks for Governance

- Brick Schema & Haystack = access + audit
- Support for RBAC + API validation
- Semantic integrity → system accountability







Designing a Secure BAS Architecture

- Segment with VLANs, firewalls, RBAC
- Patch lifecycle & encrypted logging
- Use protocol filtering at edges








RBAC & Auditability

- Tech vs Admin → limited permissions
- Audit trails, logs, traceability
- NIST, ISO, IEC support role models







Real-Time Monitoring & Incident Response

STEP2CleanPLAN

NEXT Black Sea Basin

- IDS, SIEM, log analysis in FM context
- Behavior monitoring of edge devices
- Incident playbooks and tabletop drills







Legacy Systems: Risk & Containment


- Segment, isolate, filter bridges
- Upgrade roadmap + risk heatmap
- Legacy ≠ ignored





Security by Design & Digital Twins

- Model, test, simulate security workflows
- Embed tag integrity & behavioral baselines
- Train teams with simulation insight







Ongoing Adaptation & Governance

- Patch, monitor, retrain policies regularly
- Review post-event failures
- Iterate design with new threats








Conclusion: Design for Resilience

- Security → performance + continuity
- Interoperability → clarity + maintainability
- Govern with foresight, not patchwork







Reflection Prompts

STEP2CleanPLAN

NEXT Black Sea Basin

- What risks exist due to protocol misalignment?
- How can your team support RBAC and segmentation?
- What upgrade priority should be mapped first?







Modernization Roadmap for Smart Buildings

NEXT Black Sea Basin

- Legacy → VLAN segmentation
- Intermediate: protocol filter gateways
- Future: encrypted, semantic twins









- Scan & detect threats
- Patch & document
- Train & retest teams
- Review policy post-incident

Lifecycle Update Flow









Thank you!

Q & A







STEP2CleanPlan


Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 I: Data Analytics, Fault Detection & GIS Integration

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







Agenda


- Data in Smart Building Operations
- KPIs, Dashboards, and Visualization
- Fault Detection & Diagnostics (FDD)
- Predictive Maintenance and Alerts
- GIS Mapping for Urban Efficiency
- Conclusion & Reflection





Why Data Analytics Matters

- Transforms raw data into insights
- Improves energy, comfort, uptime
- Supports long-term performance planning









- Logging: local or cloud
- APIs, middleware, storage
- Feeds dashboards and analytics

Smart Data Infrastructure







What Are KPIs in Smart Buildings?

NEXT Black Sea Basin

STEP2CleanPLAN

Energy F	Performance
-----------------	-------------

- Energy Use Intensity (EUI)
- kWh/m²/year
- Benchmark vs. Design

Comfort Metrics

- Temperature
- CO₂ Levels
- Humidity
- Occupant Satisfaction

Operational Uptime

- System Availability
- Runtime Hours
- Fault Frequency

Occupancy & Usage

- Zone Occupancy
- Occupant Density
- Schedule Alignment

GHG & Sustainability

- GHG Emissions
- Renewable Ratio
- Carbon Intensity








- Clarity over complexity
- User segmentation: FM vs admin
- Mobile vs desktop logic

Dashboards and UI Design










- Detects performance deviation
- Compares expected vs actual operation
- Flags energy waste or failure

What is FDD?








NEXT Black Sea Basin

STEP2CleanPLAN

FDD Rule Types








Root Cause Mapping

- Sensor anomaly vs equipment issue
- Control override vs actual fault
- Commissioning logs as reference








From Reactive to Predictive Maintenance

NEXT Black Sea Basin








Data-Driven Workflows

NEXT Black Sea Basin








What is GIS in the Built Environment?

STEP2CleanPLAN

Geospatial layering of assets

Environmental + building data fusion

Used in city planning + facility strategy







GIS in Smart Building Planning

- Maps usage, solar access, resilience
- Connects micro data to macro scale
- Links zoning, energy, renovation








GIS & Equity, Climate Action

STEP2CleanPLAN

Real World

- Access to cooling/ventilation by district
- Target underserved areas for upgrade
- Support just transition policies











Conclusion: Data for Smarter Performance

NEXT Black Sea Basin

- Analytics drive ZEB-readiness
- FDD and GIS → smarter investment
- Digital + spatial integration is key







Reflection Questions

NEXT Black Sea Basin

- Which data stream is most useful in your region?
- How is fault detection handled in your context?







GIS + BIM Integration: Building to District

NEXT Black Sea Basin


- GIS: zoning, solar access, utility overlays
- BIM: component-level asset modeling
- Together: lifecycle + spatial performance





Citywide Energy Use Heatmap

- Darker zones: high energy intensity buildings
- Highlight retrofit priority areas
- Supports equity & climate goals








Climate Vulnerability Mapping

- Map cooling access + heat risk by neighborhood
- Target heat islands with retrofit priority







Emerging Issue: Data Governance in Smart Cities

STEP2CleanPLAN

NEXT Black Sea Basin

- Who owns sensor data in public buildings?
- How is it anonymized, stored, reused?
- Policy frameworks lag behind tech capacity









Thank you!

Q & A







STEP2CleanPlan

Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 G: GIS Integration, Portfolio Benchmarking & Spatial Analytics

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







Agenda

- GIS in Smart Buildings
- Smart Data Layers & System Integration
- Portfolio Benchmarking with Context
- Case Examples: Greece, Finland, France
- Future Scenarios & Spatial Equity
- Conclusion & Reflection





GIS as a Strategic Tool

- Visual context for decisions
- Links assets, space, and data
- Acts as bridge across scales



https://www.esri.com/arcgis-blog/products/arcgis-online/announcements/whats-new-arcgis-online-december-2018





NEXT Black Sea Basin

Why GIS Now?

- Policies: EPBD, ZEB mandates
- Data: IoT, CMMS, BMS matured
- Scale: Sites → cities → countries







NEXT Black Sea Basin

STEP2CleanPLAN

- Comfort: CO₂, temp, RH, light
- Energy: EUI, peaks, carbon intensity
- Occupancy: sensors, Wi-Fi, schedules
- Asset info: IDs, condition, tickets

Core GIS Data Layers








From Layers to Insight

NEXT Black Sea Basin








Connecting GIS to Building Systems

- BAS/BMS: overrides, trends, faults
- CMMS: fault tickets & dispatch
- Synchronize IDs & timestamps



https://www.xyht.com/sponsored/gis-implementation-in-construction-techniques-and-benefits/






Use Cases from Integration

STEP2CleanPLAN

NEXT Black Sea Basin

- Cluster faults by equipment type/age
- Identify override zones during heatwave
- Optimize dispatch by location/SLA







CMMS Workflow from FDD

STEP2CleanPLAN

NEXT Black Sea Basin

- Fault flags via FDD logic
- Auto-ticket in CMMS w/ zone ID
- GIS confirms location, closeout logged








Portfolio Context for Decision-Making

- Normalize 100+ sites with filters
- Overlay zoning + complaints + retrofits
- Identify risk or opportunity clusters



https://link.springer.com/article/10.1007/s11356-021-14082-3






From Benchmark to Retrofit Logic

STEP2CleanPLAN

- Compare retrofit ROI across building types
- Use spatial indicators to set priorities
- Visualize decisions with outcome maps



https://experience.arcgis.com/experience/ba606f0b1a984e48a736f003aefc42c7



Case: West Attica – Schools Retrofit

- Mapped HVAC comfort violations + CO₂
- Zones near coast prioritized
- Aligned GIS with funding timeline








Case: Helsinki Smart Portfolio

STEP2CleanPLAN

- 1,300+ buildings live-tracked
- Equity overlays inform capital budget
- Supports 15-minute city access goals



https://www.mdpi.com/2624-6511/7/4/83






Case: ADEME (France) Retrofit Map

STEP2CleanPLAN

- 230K buildings, mapped EPC + retrofits
- Public + policy users access portal
- Spatial logic for national retrofit waves



https://www.geothermies.fr/comprendre/innovation/les-projets/2023-2025-geoscan-ile-de-france-ademe-region-ile-de-france-brgm






GIS + AI: Predictive Targeting

STEP2CleanPLAN

- Train patterns from fault/CO₂ data
- Predict retrofit payback and risk
- Auto-flag priority zones



https://geographical.co.uk/science-environment/danger-zones-mapping-earthquakes-in-europe






GIS as Urban Operating System

STEP2CleanPLAN

- Integrate zoning, transport, demand data
- EVs, comfort, building carbon in one map
- Core layer of digital twin governance




https://encity.co/online-gis-dashboard-for-planning-management-and-stakeholder-engagement/





Spatial Equity in Smart Planning

- Map access vs upgrades by income area
- Monitor repair lag by region
- Equity filters for capital spending



https://www.mdpi.com/2220-9964/14/4/157






Conclusion: GIS Enables Visual Intelligence

STEP2CleanPLAN

- See patterns, set priorities, build equity
- Combine tech + policy + people via space
- Plan smarter, act sooner



https://ignitarium.com/introduction-to-gis-geographical-information-system-data-its-visualization-and-processing-techniques/



NEXT Black Sea Basin

STEP2CleanPLAN

- Which of your decisions could GIS improve?
- Where could equity be spatially mapped?

Reflection Prompts







STEP2CleanPLAN

Thank you!

Q&A







STEP2CleanPlan


Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 A: Introduction to Zero Emission Buildings, nZEB Goals, and EU Directives

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







STEP2CleanPLAN

Agenda

- Why Zero Emission Buildings?
- nZEB, ZEB & Passive House Frameworks
- Policy Landscape (EPBD, Taxonomy, Renovation Wave)
- Metrics & Compliance Tools
- Implementation & National Approaches
- Passive House & Legal Alignment
- Conclusion & Reflection





Why Zero Emission Buildings?

STEP2CleanPLAN

NEXT Black Sea Basin

- 40% of EU energy use
- 36% of EU GHG emissions
- Buildings are central to 2050 neutrality








NEXT Black Sea Basin

EPBD Recast Milestones

STEP2CleanPLAN



Source: European Commission, ING





From Efficiency to Emissions

STEP2CleanPLAN

NEXT Black Sea Basin

- Old model: focus on demand
- New model: operational GHG
- Legislative and technical evolution









Performance Tiers Overview

Feature	nZEB	ZEB	Passive House (PH)
Legal Status	National Mandate	EU Directive (EPBD)	Voluntary Certification
Focus	Energy Efficiency	Operational GHG Emissions	Comfort & Demand Reduction
Verification	EPC	GHG Metrics & PED	PHPP + On-Site Testing
Renewables	Partial (varies)	Required (zero-emission)	Optional (usually included)





nZEB in Practice


NEXT Black Sea Basin

STEP2CleanPLAN

Estonia: 100 kWh/m²/year

• Ireland: 45–60 kWh/m²/year

Broad national variation











ZEB by Definition – EPBD Annex III

- Zero operational GHG emissions
- Efficient envelope and systems
- Carbon-free residual energy








Passive House Criteria

STEP2CleanPLAN

• For cold – temperate region








EPBD Recast (2021)

NEXT Black Sea Basin

- ZEB as standard → Policy shift
- Operational GHG focus → Central metric: kgCO₂eq/m²/year
- Digital tools introduced → Renovation passports,
 Smart Readiness Indicator, digital logbooks







EPBD 2024 Update

STEP2CleanPLAN

NEXT Black Sea Basin

Pillar	Description
Ⅲ MEPS Enforcement	Minimum Energy Performance Standards enforced for lowest-performing 15–20% of buildings
Public Mandates Expanded	All new public buildings must be ZEB by 2028, renovations mandated
Design Guidance Strengthened	Integrated tools: Renovation Passports, Logbooks, SRI, lifecycle thinking






EU Taxonomy & Green Finance

STEP2CleanPLAN

NEXT Black Sea Basin

- PED 10% below nZEB
- Lifecycle emissions required
- Supports climate-proof investments









Renovation Wave Strategy

NEXT Black Sea Basin

- 35M building renovations by 2030
- Focus: schools, housing, hospitals
- Scale + quality = main aims












Measuring Real Performance

- Gap between design vs reality
- Smart meters, commissioning needed
- Post-occupancy data emphasized







Operational GHG as a Metric

NEXT Black Sea Basin

- kgCO₂eq/m²/year = primary metric
- Based on national emission factors
- Defined by building type + zone











NEXT Black Sea Basin

STEP2CleanPLAN

- PED: primary energy demand
- Renewable ratio: site/nearby preferred
- Combined for ZEB evaluation

PED & Renewable Share







Compliance Tools


Tool Category	Logo/Icon	Description	
EPC Tools	SAP	Used for national certification and basic energy modeling (e.g. UK, Ireland)	
PHPP		Design tool for ultra-low energy and comfort assurance	
Dynamic Simulations	Energy Plus	Used for high-resolution, hourly simulations and public project validation	





NEXT Black Sea Basin

Post-Building Validation








nZEB Variability Across EU

NEXT Black Sea Basin

- Denmark: 20–30 kWh/m²/year
- Spain: 60–80 kWh/m²/year
- Estonia: up to 120 kWh/m²/year











ZEB Early Movers

NEXT Black Sea Basin

- Austria: GHG-linked subsidies
- Netherlands: BENG method
- France: RE2020 carbon budgets








Implementation Barriers

- Labor shortage, enforcement gaps
- Lack of verification infrastructure
- Unclear financial ROI







Best Practices Emerging

NEXT Black Sea Basin

- One-stop shops (FR, LT)
- Digital EPC + BIM (FI)
- Public procurement drivers (DE)







Passive House: Voluntary Model

- Envelope-first, demand-led
- Proven tools + QA
- No legal mandate













Policy vs Design Frameworks

ZEB (Policy Framework)	Passive House (Design Framework)			
GHG compliance goal	Comfort + demand reduction goal			
EPC / emissions thresholds	PHPP (design simulation)			
Regulated (EPBD)	™ Voluntary (PHI)			
Focus on operational carbon	Focus on demand, comfort, quality			
Compliance = documentation	Compliance = modeling + testing			






NEXT Black Sea Basin

Beyond Passive: Advanced Voluntary Standards

STEP2CleanPLAN

- PH Plus, PH Premium
- EnerPHit for retrofits
- Active House, MINERGIE





Basic requirement Very low heating/cooling demand ≤ 15 kWh/(m²a)













+ Generation of renewable energy+ higher (PER) energy efficiency

© PHI






Conclusion & Reflection

NEXT Black Sea Basin

- ZEB: regulatory shift
- National variety persists
- Which metric drives change: energy, GHG, or comfort?







ZEB Early Movers – Country Examples

- France RE2020 includes carbon budgets for all new buildings
- Netherlands BENG: primary energy, airtightness, and daylight factors
- Austria Ties subsidies to operational GHG performance








Understanding GHG & PED Thresholds

- GHG: kgCO₂eq/m²/year set by building type and climate zone
- PED: Primary Energy Demand max site+source energy
- Combined to define ZEB performance boundaries









Thank you!

Q & A







STEP2CleanPlan


Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 B: Passive House Design Principles

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







Agenda

- Why Passive House Matters
- Core Performance Metrics
- PHPP Tool Overview
- Case Study Applications
- EU Compliance Interactions
- Conclusion & Reflection






NEXT Black Sea Basin

STEP2CleanPLAN

- Voluntary, high-performance design
- Reduces demand before renewables
- Aligns with EU ZEB goals

Why Passive House Matters?



Source: PHI





Passive House Criteria

NEXT Black Sea Basin

STEP2CleanPLAN



 The values of all certified component are available in the component database and in PHPP

mponents	Source: PHI	

	Arctic	Cold	Cool- temperate	Warm- temperate	Warm	Hot	Very hot
Walls (opaque)	0.09	0.12	0.15	0.3	0.5	0.5	0.3
Glazing type recommended	Vacuum / 4-glazed low-e	3- or 4-glazed low-e	3-glazed low-e	3-glazed low-e	2-glazed low-e	2-glazed anti-sun	3-glazed anti-sun
Uw, installed MAX (vertical)	0.45	0.65	0.85	1.05	1.25	1.25	1.05






NEXT Black Sea Basin

STEP2CleanPLAN

• For cold – temperate region

- ≤15 kWh/m²/year heating & cooling
- ≤0.6 ACH @ 50 Pa
- PER ≤60 kWh/m²/year or
 PE ≤95 kWh/m²/year

Passive House Criteria








NEXT Black Sea Basin

STEP2CleanPLAN

- Stable indoor temps 20–25°C
- ≤10% hours >25°C
- Balanced MVHR with 75%+ recovery

Thermal Comfort & MVHR








Thermal Bridge-Free Detailing

- Psi-values ≤ 0.01 W/mK
- All junctions modeled
- Avoids mold, improves comfort








NEXT Black Sea Basin

What is PHPP?

- Excel-based, monthly balance tool
- Detailed input, traceable results
- Preferred for Passive House

	Treated floor area m²	175.5		Criteria	Alternative criteria	Fullfilled?2
Space heating	Heating demand kWh/(m²a)	11	≤	15	-	Yes
	Heating load W/m²	10	≤	-	10	163
Space cooling	Cooling & dehum. demand kWh/(m²a)	-	≤	-		-
I	Frequency of overheating (> 25 °C) %	1	≤	10		Yes
Frequency of exc	cessively high humidity (> 12 g/kg) %	0	≤	20		Yes
Airtightness	Pressurisation test result n ₅₀ 1/h	0.6	≤	0.6		Yes
Non-renewable Prima (PE)	ary Energy PE demand kWh/(m²a)	58	≤	-		-
Primary Energy Renewable (PER)	PER demand kWh/(m²a)	58	≤	60	60	Yes
	denew. energy generation (in rel. to projected building footprint area) kWh/(m²a)	13	≥	-	-	










- U-values, window specs, MVHR, shading
- Climate file and occupancy
- Ventilation and airtightness data

PHPP Inputs










- Heating/cooling demand
- Overheating % and PER
- Ventilation efficiency

PHPP Outputs








NEXT Black Sea Basin

STEP2CleanPLAN

- Envelope tuning (WWR, shading)
- Optimizing MVHR and systems
- EnerPHit upgrade modeling

PHPP and Iterative Design



Source: PHI





Lodenareal – Innsbruck (PH Classic)

- Build type: apartment house
- 361 units
- Air tightness: $n_{50} = 0.18/h$ test result
- Annual heating demand:
 14 kWh /(m²a) calculated according to PHPP
- Heating load: 9 W/m²
- PE demand: 117 kWh /(m²a) calculated according to PHPP on heating installation, domestic hot water, household electricity and auxiliary electricity calculated
- Building structure costs (gross)1600 €/m² Treated Floor Area according to PHPP








Zaragoza – Spain (PH Classic)

NEXT Black Sea Basin

- ClimateWarm, temperate
- Air tightness $n_{50} = 0.3/h$
- Annual heating demand: 12 kWh /(m²a)
 calculated according to PHPP
- Heating load: 10 W/m²
- PE demand (non-renewable Primary Energy): 87 kWh /(m²a) on heating installation, domestic hot water, household electricity and auxiliary electricity calculated according to PHPP
- PER demand (renewable Primary Energy): 53 kWh /(m²a) on heating installation, domestic hot water, household electricity and auxiliary electricity calculated according to PHPP
- Generation of renewable energy: 0 kWh /(m²a) based on the projected area
- Cooling load7 W/m²
- Cooling and dehumidification demand: 10 kWh /(m²a) calculated according to PHPP







Şile, İstanbul – Türkiye (PH Plus)

STEP2CleanPLAN

Heating: 9 kWh/m²a

Cooling: 9 kWh/m²a

RE Generation: 53 kWh/m²a

External Wall U-Value: 0.102 W/m²K

Ground Floor U-Value: 0.110 W/m²K

Roof U-Value: 0.113 W/m²K

Window U-Value: 0.8 W/m²K

Heat Recovery Efficiency: 86%

Air tightness $n_{50} = 0.6/h$








Lessons Across Projects

- Early integration: success
- PHPP supports reliability
- Construction execution matters








How PH Aligns with EPBD

STEP2CleanPLAN

NEXT Black Sea Basin

- Ultra-low demand meets ZEB targets
- PHPP transparency supports QA
- Measured performance → reliable output









- No native GHG reporting
- Not accepted as EPC substitute
- No embodied carbon coverage

Where PH Falls Short










- Add emissions calcs to PHPP
- Dual tracking with EPC tools
- Use Level(s) for whole-life indicators

Bridging the Gap








PHPP vs Real Energy Use Example

NEXT Black Sea Basin

- PHPP modeled: 11,9 kWh/m²a
- Measured: 13,3 kWh/m²a
- Small deviation shows reliable forecasting










Passive House vs Local Norm Conflicts


STEP2CleanPLAN

- PH requires low demand, but may conflict with:
- Local SHGC limits (cooling zones)
- EPC modeling software assumptions

- Building form or site restrictions











NEXT Black Sea Basin

Passive House Classes: Classic, Plus and Premium







Conclusion & Reflection

STEP2CleanPLAN

NEXT Black Sea Basin

- PH: consistent high performance
- Not a law, but a method
- What would boost PH adoption in your region?









Thank you!

Q & A







STEP2CleanPlan

Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 C: Retrofitting and Construction for Zero Emission Performance

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







Agenda

- Why Retrofit for Zero Emission Goals?
- Envelope First: Insulation & Airtightness
- Ventilation, Windows, and HVAC Integration
- Retrofit Workflow & Coordination
- EnerPHit and Staged Sequencing
- Case Strategies for Real-World Success
- Conclusion & Reflection





The Retrofit Imperative

- 85% of buildings pre-modern codes
- Still in use by 2050
- Renovation: climate strategy




















Deep Retrofit Benefits

STEP2CleanPLAN

- Up to 80% GHG reduction / 85% energy consumption reduction
- Improved comfort, durability
- Supports energy poverty relief



before





- basement insulated
- walls insulated
- Passive House windows
- ventilation with highly efficient heat recovery

Photos and diagram: © Schulze-Darup





Why Shallow Renovations Fail

- Boiler/window swaps ≠ performance
- Miss airtightness, ventilation
- Lack of systems integration








Envelope as Retrofit Foundation

- Thermal enclosure comes first
- Insulation, airtightness, bridge-free
- Enables other systems to perform








Insulation Best Practices

STEP2CleanPLAN

- Continuity > thickness
- External preferred (e.g., ETICS)
- U-values: wall 0.10–0.15, roof 0.08–0.12

Typical U-values and insulation thickness for a Passive House building in Central Europe







Airtightness Detailing

- EnerPHit: ≤1.0 ACH @ 50 Pa
- Defined layer, taped transitions
- Pre/post blower door tests












STEP2CleanPLAN

- Ψ-values < 0.01 W/mK
- Sill/jamb/foundation wraps
- Modeled with THERM or Flixo

Thermal Bridge Elimination



The insulating envelope encloses the entire heated volume.

Thermal bridge-free design: $\Psi_e \le 0.01 \text{ W/(mK)}$

Avoidance Rule:

The insulating envelope should not be interrupted if this can be avoided.

Penetration Rule:

If penetration of the insulating layer is unavoidable, the thermal conductivity of the penetrating material should be as low as possible.

Use porous concrete or even better wood, or PUR or foam glass elements.

Connection Rule:

Insulation layers at building component connections merge into each other over the entire surface without interruption.

© PHI






STEP2CleanPLAN

- Windows before insulation
- Air barrier before finishes
- Insulation after prep/testing

Sequencing Envelope Work



Figures © Passivhaus Institut





Planning & Verification Tools

- Airtightness plans, thermal modeling
- Blower door, infrared camera
- U-value calculations








STEP2CleanPLAN

- $U \le 0.85-1.0 \text{ W/m}^2\text{K}$, triple-glazed
- Orientation: SHGC strategy varies
- Air/thermal continuity at frame

High-Performance Windows








STEP2CleanPLAN

- Small systems for small loads
- Prefer heat pumps, low-temp delivery
- Smart zoning, defrost readiness

HVAC for Passive Loads







Whole-System Synergy

NEXT Black Sea Basin

STEP2CleanPLAN







Envelope enables ventilation


Ventilation stabilizes air quality

Systems right-sized by PHPP



Retrofit Workflow Logic

- Diagnostics → Design → Envelope → MVHR → QA
- Air test before finishes
- PHPP modeling aligns each step







Contractor Risk Mitigation

- Pre-start workshops/mockups
- Annotated site drawings
- Passive House trained crews







STEP2CleanPLAN

- Upfront cost + time = higher
- But lifecycle + ROI = strong
- Use energy + comfort gains to sell

Budget & Time Pressures










STEP2CleanPLAN

- Flexible: phased or full
- 25 kWh/m²/year heating target
- Allows component upgrades

EnerPHit Principles








Phased vs Whole-Building Approach

- Staged = budget/practicality
- PHPP supports step-by-step
- Requires airtightness foresight







Apartment Building Hofheim, Taunus


NEXT Black Sea Basin

STEP2CleanPLAN









Interreg NEXT Black Sea Basin Programme is co-financed by the European Union under the Neighbourhood, Development and International Coope participating countries: Armenia, Bulgaria, Georgia, Greece, Moldova, Romania, Türkiye and Ukraine.




Retrofit Project, Tevesstrasse, Frankfurt, Germany


STEP2CleanPLAN

Retrofit Project, Tevesstrasse, Frankfurt













Reflection Prompt

STEP2CleanPLAN

NEXT Black Sea Basin

- Where do YOU hold leverage?
- Detailing? QA? Coordination? Client framing?








Contractor Training & Construction Mockups

STEP2CleanPLAN

NEXT Black Sea Basin

- Passive House—aligned training improves quality
- Mockups for complex joints (e.g. floor-wall-air barrier)
- Toolbox talks: align sequences, reduce clashes









STEP2CleanPLAN

Thank you!

Q&A







STEP2CleanPlan


Module 2: Sustainable Urban Mobility and Energy Efficiency

Sub Module 202: Energy Efficiency in Urban Infrastructure

202 E: Sensors, IoT Devices & Control Strategies

Trainer:

COOPERATION FOR SUSTAINABLE ENERGY AND CLIMATE ACTIONS PLANNING AND MONITORING IN BSB







STEP2CleanPLAN

Agenda


- Sensor Fundamentals
- Types and Applications
- IoT Devices & Network Logic
- Control Strategies & QA
- Override Failures & Fusion Logic
- Security, Calibration & Reflection
- Conclusion & Reflection





Why Sensors Are Foundational

- Enable automation and efficiency
- Connect user comfort to system logic
- Basis for BAS and smart operation








Sensors in EU Policy Frameworks

NEXT Black Sea Basin










Common Sensor Types in Smart Buildings

NEXT Black Sea Basin

- Temperature / Humidity
- CO₂ / VOC / IAQ
- Occupancy / Motion / Presence








STEP2CleanPLAN

- Light, sound, vibration
- Smart meters and submeters
- BTU, flow, water use

Specialized & Energy Sensors










STEP2CleanPLAN

- Combined: CO₂, temp, motion
- Enable predictive logic
- Reduce installation points

Multi-Sensor Devices



https://www.researchgate.net/figure/The-multi-sensor-PCB-board-includes-three-OF-sensors-an-illuminance-sensor-based-on-a_fig4_232656243






What Makes a Device 'IoT' in Smart Buildings?

NEXT Black Sea Basin

- Sensing + communication
- Cloud-ready, edge-aware
- Often wire-free and self-powered









STEP2CleanPLAN

- Edge > Gateway > Server
- Distributed data and control
- Supports zoning and local override

Smart Building IoT Topologies










STEP2CleanPLAN

- Zigbee: short-range, mesh
- LoRaWAN: long-range, slow data
- BLE / WiFi / Thread trade-offs

IoT Protocol Comparison








STEP2CleanPLAN

- Authentication, encryption
- Firmware update cycles
- Risk from default credentials

Security in IoT Devices








What is a Control Strategy?

NEXT Black Sea Basin

- Rule or logic-based response
- Sensors feed decisions
- Key to ZEB-ready operation








Types of Control Logic

STEP2CleanPLAN

- On/Off (bang-bang)
- Schedule / Occupancy
- PID loop tuning



Equipment or Process Variations

https://www.wevolver.com/article/pid-loops-a-comprehensive-guide-to-understanding-and-implementation





Tuning and Commissioning

- Each sensor/control link calibrated
- QA pre-checks, field override testing
- Logging and data integration







STEP2CleanPLAN

- Manual setpoint changes
- Occupant override loops
- Disconnected logic → inefficiency

Override & Drift Scenarios








STEP2CleanPLAN

- Sensor drift / misplacement
- Network dropout / stale data
- Firmware bug in actuator response

System Failure Risks








Sensor Fusion → Multivariable Logic

- Combines temp + CO₂ + motion
- Used for adaptive HVAC, lighting
- Basis for predictive analytics







Examples of Fusion in Control

STEP2CleanPLAN

NEXT Black Sea Basin

- CO₂ + occupancy → ventilation trigger
- Lux + motion → lighting dimming
- IAQ + thermal → window opening









Conclusion: Reliable Sensing → **Reliable Buildings**

- Sensors → performance gatekeepers
- Control → balancing comfort + policy
- QA, tuning, security → success









STEP2CleanPLAN

- Where is your biggest sensor risk?
- Which controls fail silently in your region?
- Where can IoT or fusion logic add value?

Reflection Prompts







Long-Term Sensor Drift

- CO₂ sensor baseline rises after 18–24 months
- Humidity sensors drift due to particulate buildup
- Requires scheduled recalibration (1–2 years typical)








Example: Manual Override Causing Energy Waste

- Office user overrides setpoint to 23°C all summer
- BAS fails to revert logic due to access settings
- Energy spike + discomfort in adjacent zones








Sensor Commissioning QA Checklist

- Checklist: location, label, response time, paired device
- Cross-reference with control input and visual tag
- Trend chart shows baseline test data








Multivariable Fusion: Adaptive Ventilation Logic

- $CO_2 > 900 \text{ ppm} \rightarrow \text{base ventilation trigger}$
- VOC detected → add 30% airflow
- Occupancy signal absent → delay ramp-up









STEP2CleanPLAN

Thank you!

Q & A

